

**Product group** Self Adhesive Vinyl Repair Patches

---

**Product description** Our aggressive adhesive sticks to almost any surface and can be used for a variety of flexible, long lasting repairs! Our non-gloss matte finish is almost invisible, eliminating the need to match colours on fabric and other materials. Tenacious™ Patches stops rips from spreading and adds abrasion resistance to high wear areas of garments and gear. Provides fast, long lasting repairs on synthetic and natural fabrics, fleece, vinyl, rubber and plastic. Ideal for tents, rain gear, backpacks, sleeping bags, mats and pads, seats, awnings, soft coolers, inflatable toys, emergency bicycle tyre repairs etc.

Special features

- sticks to most surfaces
- water resistant
- semi transparent
- very low volatiles

---

**Surface condition** Clean and dry surface, before application.

---

**Instructions for use**

— Application Clean and dry area to be repaired. Trim loose threads. Join torn edges of material. Cut tape to appropriate size, overlap repair at least 25mm (1 in.) in all directions. Remove paper backing and apply patch to damaged area. Patch may be applied to outside surface or inside surface. After applying, rub patch with pressure using circular motion from centre out. Item may be used immediately. Adhesive reaches full strength in 24 hours.

---

Typical general characteristics	Composition	by weight
	Fibre reinforced PVC film	40%
	Pressure sensitive adhesive	20%
	Backing Paper	40%

---

**Storage and Care** Store in a cool, dry place. The recommended storage temperature is 5 – 30 °C. Store in plastic bag. Tape is washable. Do not dry clean

---

# Tenacious Sealing & Repair Patches

## Technical Data Sheet

### **Packing & Size**

3 Transparent patches + 1 Black patch in Clamshell @ 96 per box.

---

### **Safety precautions**

No personal protection required. Very sensitive person might show irritation after skin contact with the adhesive. Do not use on mouth, nose and eyes . Keep out of the reach of children. Fire Fighting Measures Extinguishing Media: water or foam. Hazardous Decomposition Products in case of fire: CO, CO<sub>2</sub>, Oxides of nitrogen, HCl- gas

---

### **Warranty**

The information provided is to the best of our knowledge. However, we, do not assume legal responsibility for use or reliance there on. We disclaim all warranties expressed or implied including the fitness for a particular purpose. Data may be subject to modification without previous notice. Please check validity.

---

For additional information, please contact:  
McNett Europe  
P.O. Box 11 27, D-29664 Walsrode/ Germany  
e-mail: [mark@mcnetteurope.com](mailto:mark@mcnetteurope.com)

# Aquasure® Toluene Free Data Sheet